Ultra-M

Our most versatile dissolver ever.

Unmatched flexibility and reliability

The Ultra-M is the flagship model of the enduroTEQ[™] series. It utilizes a non-electric mechanical level system and integrated flow control to provide accurate chemical dosing for a variety of water treatment systems.



Built with durable HDPE injection molded body components and high quality chemical resistant materials, you can be confident in its performance regardless of environment or chemical choice.

Whether you are panel-mounting or field erecting, installations are a breeze. The sleek, compact design of the Ultra-M allows for installation in tight spaces and is capable of treating systems both large and small. The dissolver is designed to couple easily so the system can be expanded to treat even the largest boiler and cooling systems.

A chemical pump is required for efficient delivery of the solution created by the dissolver. Please refer to <u>SolidGuide</u> to generate a site survey and recommendations on pump sizing when choosing the correct pump for your installation.

SYSTEM SPECIFICATIONS

| Net weight | 9.6 lb | Flow rate | 0.45 GPM |
|--------------------------------------|-------------------------|----------------------------|----------------------|
| Ship weight | 13.0 lb | Spray nozzle | Form Specific |
| Dimensions | 10" W x 23" H x 13.5" D | Mounting | 3 screws and anchors |
| Minimum water line requirement | 3/8" | Assembly & install time | 10 minutes |
| Water pressure | 20 psi - factory set | Electrical requirements | N/A |

PRODUCT FEATURES





